



# THE AVEDØRE PROJECT

HOW TO FIND RENEWABLE BIOGAS SOURCES AND INTEGRATE THEM IN THE GAS GRID BY UPGRADING AND METHANIZATION WITH NEW TECHNOLOGIES.

Authors:

Henrik Rousing, Planner, HMN Gashandel A/S
Dines Thornberg, Development Manager, BIOFOS A/S





#### HMN Naturgas I/S at a Glance;

Owned by 57 municipalities in Mid-North Jutland and the Greater Copenhagen Region (unlimited partnership)

Owns the Supply Companies (limited)

- -HMN Gassalg A/S (retail)
- -HMN Gashandel A/S (wholesale)

#### HMN Naturgas I/S (Distribution)

Customers: 253.008, Distributed volume: 1.611 mio. m<sup>3</sup>

Turnover: 617 mio. kr., Net debt: 1.204 mio. kr.

Employees: 301

#### HMN Gassalg/Gashandel A/S (Sales)

Custumers: 237.360, Sales volume: 1.133 mio. m<sup>3</sup>

Turnover: 4.673 mio. kr.

**Employees: 61** 


#### The HMN Concern

Net debt: 580 mio. kr.


2013



#### The Project










#### **BIOFOS**

WWTP Avedøre, WWTP Damhusåen and WWTP Lynetten Owned by 15 municipalities.

At the 3 plants they treat 130 million cubicmeter wastewater/yearly

"Suppliers" 1,4 million people in Greater Copenhagen






**Tivoli Congress Center** 




## **Wastewater Treatment Plant Avedøre**





# Principle for the Heat Recovery and Balance








#### Project ENZUP

#### **ENZYMATIC BIOGAS UPGRADING**





- •41 MDKK (5,5 million €) three-year demonstration project for enzymatic biogasupgrading.
- Supported by EUDP with 21 MDKK (2,8 million €)
   (Danish Energy Agency's
   Energy Technology Development and Demonstration Programme)
- Target; reduced upgrading cost
- •Benefits; lower cost ⇔ more green gases

Enzymes accellerate processes.

Carbonic Anhydrase accellerate  $CO_2$  absorbtion up to 10  $^6$ .

#### **Key figures**;

Up to 2,6 million m3  $CH_4$  (300 m3/h) Quality: > 98 % target 99,9 %  $CH_4$ Rawgas ~ 60 %  $CH_4$ 









www.enzup.com











#### Highlights from the Wind- and Powersystem im Denmark





#### Project Power-to-Gas





## "System Integration"

#### **Key figures**;

1 MW electrical input Alkaline electrolysis and biological methanation

#### Power-to-CH<sub>4</sub> Efficiency:

- 78% (incl. heat recovery)
- 58% (excl. heat recovery)

#### Microorganism

- Methanogenic archaea
- Selectively evolved, not genetically modified
- Thermophile (60-65° C)
- Properties:
  - Robust (tolerant to contamination)
  - Long-lived (self-replicating)
  - Efficient (long doubling time)
  - Dynamic (short ramp rate)
  - Selective (100% methane)


















## GRID INJECTION FACILITY





#### **Grid Connection;**

From Injection Station to existing Grid and new costumers


#### **Injection Station**;

Doubble line Injection Station for two seperat gasstreams, one line out.

Gascromatographs Flowmeters Dewpoint


Odourisation

3-way valve to reject off spec gas.





Connection-point to Danish Gas Grid







# Thank you for your patience Questions?

See more at

www.enzup.com

www.biocat-project.com

and at session W4-4 and W3-4

